

HydraGEN™

HG-C Series HG4C24NA



Technical Data

| | |
|--------------------------------|---------------------|
| Diesel Engine Suitability | 30 - 60 L |
| Electrolyte Medium | Potassium Hydroxide |
| Power Consumption | 336 - 720 W |
| Power Supply | 24 VDC |
| Power Draw | 14 - 30 A |
| Environment Temperature (min.) | -40°C -40°F |
| Environment Temperature (max.) | 50°C 122°F |

Logistic Data

| | |
|-------------------------------------|--|
| Dimensions (W x D x H) | 1118 x 584 x 648 mm 44 x 23 x 25.5" |
| Unit Weight | 187 kg 412 lbs |
| Packaging Dimensions (H x B x T) | 1499 x 787 x 1143 mm 59 x 31 x 45" |
| Weight Including Packaging | 290 kg 640 lbs |
| Units per Pallet | 1 |
| Pallet Type/Size | Custom |
| Harmonized Tariff Code | 8543 3070 |

Exterior Details

| | |
|-------------------------------|---|
| Housing | Steel Chest |
| Re-Filling Requirement | 17 L Distilled Water 175 hr between refill |
| Distilled Water Refill Method | Remote fill with pump |

Convenience

| | |
|---------------|---|
| Communication | Cellular |
| Tracking | GPS |
| Other | HydraGEN™ App HydraLytica™ Driver notifications |


Applications



Power Generators



Mining Equipment



Construction Equipment